

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number  
**WO 2005/087541 A1**

(51) International Patent Classification<sup>7</sup>: **B60P 7/08**

(21) International Application Number:  
PCT/US2005/007355

(22) International Filing Date: 4 March 2005 (04.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/550,788 5 March 2004 (05.03.2004) US

(71) Applicant (for all designated States except US): **HOLLAND COMPANY LP** [US/US]; 1000 Holland Drive, Crete, IL 60417 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BREWSTER, John** [US/US]; 2060 Hawthorne Road, Homewood, IL 60430 (US).

(74) Agent: **BREZINA, David, C.**; P.O Box 2786, Chigago, IL 60690-2786 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**


— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

[Continued on next page]

(54) Title: MULTIPURPOSE LADING TIE ANCHOR SYSTEM FOR SECURING CARGO



(57) Abstract: An anchor (10) with a shaped aperture (15) that receives various and multiple types of tie straps (25)(32)(33) and strap hardware end comprised of straps of woven webbing with or without a hook or pin end, or straps of the one-time useable steel banding type. The tie strap (25)(32)(33) being held in place by the appropriate anchor provision and the said anchor being contained within a pocket in the wall (21) or floor (20) of railway box or flat car (84). Various industry lading tie straps, bands, strap end pin or strap end hooks already in use are allowed to be connected to the shaped aperture anchor. An appropriate ratchet inherent to the specific type of tie strap being used is operated to remove any remaining slack in the lading ties (25)(32)(33) and then apply the desired tension thereon to secure the lading to the railway car.

WO 2005/087541 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*